

HT-HB02-XY

info@skyled.pk

High bay light



This premium High Bay Light provides ultra-bright output with low energy consumption, making it ideal for warehouses and factories. Its rugged design and wide beam coverage ensure maximum visibility and safety.

HT-HB02-XY

info@skyled.pk

High Bay Light	
General Characteristics	
Product Code:	HT-HB02-150W
Material:	Aluminum
Grade:	Industrial
Rated Life:	50,000 hours
Protection:	IP 66
Warranty:	2 Years
Make:	SKYLED
Optical Characteristics	
Beam Angle:	90°
Color (CCT):	4000K
CRI:	> 80
Source:	Lumileds
LOR:	>90%
Lumens:	160lm/W ±05%
Cover Optics	PC Lens
Electrical Characteristics	
Wattage:	150W
LED Driver:	SKYLED/Moso/Equivalent
Input Voltage:	AC 100V - 277V
Frequency:	50 TO 60Hz
Working Temp:	-20° C 50° C
Power Factor:	>0.95
Energy Saving:	Up to 80%
Compliance:	CE, RoHS

HT-HB02-XY

info@skyled.pk

This LED high bay light is suitable for:

- Warehouses
- Factories & industrial units
- Workshops
- Manufacturing plants
- Parking garages
- Shopping malls
- Exhibition halls
- Gymnasiums & sports halls
- Supermarkets
- Airports & railway stations
- Cold storage facilities
- High-ceiling indoor areas

Key Features for Applications

- High brightness and energy saving
- Wide beam angle for large area coverage
- Long lifespan with low maintenance
- Efficient heat dissipation
- Suitable for high mounting heights
- Industrial-grade durable design



Safety First

Turn off the power at the main circuit breaker, not just the wall switch.

Use a voltage tester to confirm the fixture is dead before touching wires.

Turn the power back ON.